

# Water Quality Turbidity Meter

## Thermo Scientific Orion AQUafast IV AQ4500 Turbidimeter

The Orion AQ4500 Turbidimeter offers advanced features not available on any other benchtop or portable turbidimeter. The AQ4500 offers a dual source LED which allows readings that comply with both EPA 180.1 and ISO 7027. Turbidity can be read in the range of 0-1000 NTU with a choice of units: NTU, FAU, FNU, ASBC, and EBC. In the range of 0-40 NTU the AQ4500 offers a ratiometric range which will give EPA, GLI method 2 equivalent numbers.

This portable field unit is truly IP67 waterproof with typical battery life over 1000 hours on one set of batteries and datalog capacity of 100 points which can later be downloaded to a printer or computer. The AQ4500 accepts 24 mm cuvettes and comes with a two year warranty.

### FEATURES

- Nephelometric and Ratiometric measurements with Autoranging
- Data log capacity of up to 100 data points
- Readings in the range of 0-1000 NTU with a choice of units: NTU, FAU, FNU, ASBC, or EBC
- Includes Turbidity Standards kit, rugged carrying case, and replacement cuvettes
- Orion AQ4500 is IP67 waterproof to a depth of 3 meters



### SPECIFICATIONS

<b>Type:</b>	Turbidity Meter	
<b>Principle of Operation:</b>	Nephelometric	
<b>Operating Modes:</b>	Automatic	
<b>Measurement Modes:</b>	Automatic	
<b>Ranges:</b>	<b>NTU</b>	0 - 2000
	<b>Nephelometric</b>	0 - 4000
	<b>EPA 180.1</b>	0 - 4000 NTU
	<b>ISO-NEPH (7027)</b>	0 - 150 FNU
	<b>ISO-ABSB</b>	40 - 4000 FAU
	<b>IR-RATIO</b>	0 - 4000 NTU
	<b>EBC</b>	0 - 24.5 EBC
	<b>ASBC</b>	0 - 236 ASBC
<b>Accuracy:</b>	± 2% of reading plus 0.01 NTU (0 - 500 NTU) ± 3% of reading (500 - 1000 NTU) ± 5% of reading (1000 - 2000 NTU)	
<b>Resolution:</b>	0.01 NTU (0 - 9.99) 0.1 NTU (10 - 99.9) 1 NTU (100 - 1000)	

<b>Repeatability:</b>	± 1% of reading or 0.01 NTU
<b>Response Time:</b>	< 8 seconds
<b>Calibration:</b>	1, 10, 100, 1000 NTU
<b>Signal Averaging:</b>	Yes
<b>Sample Cell Size:</b>	24 mm
<b>Sample Size:</b>	Approx 12 mL
<b>Display:</b>	Custom LCD
<b>RTC:</b>	Yes
<b>Input/Output:</b>	RS-232 Serial Port
<b>Power:</b>	Battery – four AA's (2,500 hours Alkaline, 10,000 Lithium)
<b>Environmental Conditions:</b>	
<b>Operating Temperature</b>	-40° to 140°F (-40° to 60°C)
<b>Humidity</b>	90% relative humidity at 30.0°C max
<b>Light Source:</b>	Light Emitting Diode (LED)
<b>Warranty:</b>	2 years
<b>Weight:</b>	8 lbs. (3.63 kg)
<b>Safety Rating:</b>	UL, CSA, CE, FCC

**CALL GEOTECH TODAY (800) 833-7958**

**Geotech Environmental Equipment, Inc.**

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • **(800) 833-7958** • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com